

CUT REFLEX + REFLECTIVE TAPE

Cut reflex is a highly-durable, laser-cut vinyl that's designed for intense environments. Cut reflex contains a reflective material that's ideal for heavy workwear and functional garments.

Cut Reflex is best suited for situations when there is a requirement for heat transfer with certified reflective capability.

PROPERTIES



Environmental cert.
 STANDARD 100 by
 OEKO-TEX® class 1



Certificate
 EN 20471 / ANSI 107



ISO Certificate
 ISO 3175



Washing durability
 Up to 75°C



Tumble drying
 Up to 75°C



Ironing
 only on the inside
 of the garment



Application temp.*
 130°C



Application pressure*
 2 - 6 bar



Application time*
 15 sec + 15 sec








* These specifications are only intended as recommendations. Certain deviations in temperature, time & pressure may occur, depending on the material.

AVAILABLE COLOURS

 SILVER

APPLICATION INSTRUCTIONS

The following basic settings are suitable for the majority of textiles.

- | | | | |
|---|---|---|---|
|  Temp.
130°C |  Time
15 seconds |  Pressure*
2 - 6 bar |  Remove the Plastic carrier
Immediately after application. |
|---|---|---|---|
- | | | | |
|--|---|---|---|
| Reheat
(Without plastic carrier) |  Temp.
130°C |  Time
15 seconds |  Pressure*
2 - 6 bar |
|--|---|---|---|

*The standard setting for a small base plate is 2-3 bar and 4-6 bar for a large base plate. When using a heat press from a manufacturer other than Hot Screen, the pressure should be set to 0.5-1.5 kg/cm2.

