

## CUT REFLEX + REFLECTIVE TAPE

Cut reflex is a highly-durable, laser-cut vinyl that's designed for intense environments. Cut reflex contains a reflective material that's ideal for heavy workwear and functional garments.

Cut Reflex is best suited for situations when there is a requirement for heat transfer with certified reflective capability.

### PROPERTIES



**Environmental cert.**  
 STANDARD 100 by  
 OEKO-TEX® class 1



**Certificate**  
 EN 20471 / ANSI 107



**ISO Certificate**  
 ISO 3175



**Washing durability**  
 Up to 75°C



**Tumble drying**  
 Up to 75°C



**Ironing**  
 only on the inside  
 of the garment



**Application temp.\***  
 160°C



**Application pressure\***  
 2 - 6 bar



**Application time\***  
 15 sec + 15 sec








\* These specifications are only intended as recommendations. Certain deviations in temperature, time & pressure may occur, depending on the material.

### AVAILABLE COLOURS

 SILVER

### APPLICATION INSTRUCTIONS

The following basic settings are suitable for the majority of textiles.

1. |  **Temp.**  
130°C |  **Time**  
15 seconds |  **Pressure\***  
2 - 6 bar |  **Remove the Plastic carrier**  
Immediately after application.
2. | **Reheat**  
(Without plastic carrier) |  **Temp.**  
130°C |  **Time**  
15 seconds |  **Pressure\***  
2 - 6 bar

\*The standard setting for a small base plate is 2-3 bar and 4-6 bar for a large base plate. When using a heat press from a manufacturer other than Hot Screen, the pressure should be set to 0.5-1.5 kg/cm2.

